

# Product Specifications

## TPD-65MINI



The TPD-65MINI features a 1/3 inch Sony super HAD II CCD producing 650 TVL high-resolution images with a 3.6mm fixed wide angled lens. This camera is professional grade and includes advanced functionality such as, Day/Night, 0.0001Lux sensitivity ATW / AWC / Manual White Balance, selectable Back Light Compensation, Privacy Masking, On-Screen Display and much more. The camera is adjustable via a 3-Axis Bracket and is housed in a modern, stylish housing. The SVD-65MINI operates on 12VDC and produces stabilized Images using a flickerless function. The SVD-65MINI is easy to install, maintain and setup. It is perfect for any indoor installation where high resolution is important.

### FEATURES

- 650 TV Lines
- 1/3" SONY Super HAD II CCD
- Built-in Fixed Lens (f=3.6mm)
- Min. illumination: 0.000001Lux
- Back Light Compensation
- Stabilized images by reducing flickering
- Automatic White Balance / Automatic Gain Control
- 93X64mm Dome Size

<b>MODEL:</b>	<b>TPD-65MINI</b>
<b>PICK UP ELEMENT:</b>	1/3" Sony SuperHAD II CCD
<b>HORIZONTAL RESOLUTION:</b>	650 TV Lines
<b>EFFECTIVE PIXELS (H * V):</b>	PAL: 752 (H) x 582 (V) 440K NTSC: 768 (H) x 494 (V) 380K
<b>SCANNING FREQ' (H x V):</b>	NTSC: 15.734 KHz x 59.94 Hz PAL: 15.625 KHz x 50 Hz
<b>CCD TOTAL PIXEL:</b>	NTSC: 811(H) X 508(V) 410K PAL: 795(H) X 596(V) 470K
<b>SCANNING SYSTEM:</b>	2:1 Interlace
<b>MINIMUM ILLUMINATION:</b>	0.000001Lux (f1.2)
<b>SYNCHRONOUS SYSTEM:</b>	Internal
<b>AUTO ELECTRONIC SHUTTER:</b>	NTSC: 1/60s ~ 1/100,000s PAL: 1/50s ~ 1/100,000s
<b>VIDEO OUTPUT:</b>	1.0 Vp-p, 75 Ω
<b>S/N RATIO:</b>	More than 48db (AGC OFF)
<b>FOCUS:</b>	Manual
<b>WHITE BALANCE:</b>	Auto
<b>BACK LIGHT COMPENSATION:</b>	Auto
<b>GAIN CONTROL:</b>	Auto
<b>IN/OUT CONNECTOR:</b>	Power (Red jack), Video (Yellow jack)
<b>LENS:</b>	Fixed Lens (f=3.6mm)
<b>DIMENSION (mm):</b>	93(ø) x 64(H) mm
<b>POWER CONSUMPTION:</b>	Less than 150mA
<b>POWER SUPPLY:</b>	9VDC~15VDC (Recommended 12VDC)