

Specification

Model	OD-CM600IR50-B
Pick Up Element	CMOS 1/3"
Effective Picture Elements (H*V)	NTSC:811×508, PAL:795×596
Horizontal Resolution	600 TV Lines
S/N Ratio	More than 48dB
Clock Frequency (MHZ)	NTSC:28.636 , PAL:28.375
Scanning System	2:1 interlace
Minimum Illumination	0 Lux (with IR LED ON)
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC:1/60s~1/100,000s,PAL:1/50s~1/100,000s
Gamma Characteristic	0.45
IR Project Distance	20 Meters (with 23 Unit Infrared LED)
IR Status	Under 10 LUX by CDS
IR Power On	CDS Auto Control
Video Output	1Vpp,75 Ω
Auto Gain Control	Auto
Power/Current	12VDC(+/-10%)/ 300mA
Lens	3.6 mm
Dimension (mm)	∅ 94×68.5(H)
Weight (g)	650
Storage Temperature	-30~ +60℃
Operating Temperature	-10~ +45℃

Packing List

No	Name	Model	Number
1.	Aluminum Dome Day&Night IR Color Camera	OD-CM600IR50-B	1
2.	UserGuide	OD-CM600IR50-B Series	1