

Product Specifications

IPOF-EL1MPIR30-W

Features:

**1/3" 1.3Megapixel Aptina CMOS, Desktop IP Camera
H.264 & MJPEG dual-stream encoding, Wi-Fi Capable**

- 1.3MP Desktop Network IP Camera
- 1/3" 1.3MP Aptina CMOS Sensor
- High Performance Texas Instruments DaVinci Series DSP
- Wi-Fi Capable
- Two-Way Audio, Built in Speaker & Microphone
- 30FPS@720P
- 3.6mm Fixed Lens
- ICR Filter, Auto Iris
- White LED Illumination Distance : 30'
- PIR Sensor Range : 6m
- DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC
- 12VDC
- Built in Web Server, NVR, TechproSS (SmartPhone) & PSS
- ONVIF



Sensor Type	1/3" 1.3 Megapixel Aptina CMOS
Digital Signal Processor	TiDavinci
Effective Pixels	1280 (H)×960(V)
Image Resolution	1.3M (1280/960) / 720P(1280×720) / D1(704×576/704×480)
Encoding Speed	1.3M+ D1 (1~15fps), 720P+D1 (1~30fps)
Bit Rate	128Kbps~8192Kbps
Snap Shot	1fps JPEG capture
Scanning System	2:1 Interlace
Electronic Shutter	Auto/Manual, 1/3~1/10,000
Lens Mount	M12
Minimum Illumination	0.1 Lux F/1.8 (Color) , IR Range 10m
Signal Noise Ratio	>50dB

Product Specifications

IPOF-EL1MPIR30-W

White Balance	Auto/Manua
Noise Reduction	2D
Auto Iris	H.264/JPEG/MJPEG
Lens	3.6mm Fixed
Video Compression	H.264/JPEG/MJPEG
Audio	Built in Microphone, Built in Speaker
Audio Compression	G.711a / G.711u (64kbps) / PCM (128kbps)
Ethernet	RJ-45 (10/100 Base-T)
Network	RJ-45 10M/100M UTP
Network Functions	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server
Remote Operations	Monitor, Playback, System setting, File download, Log information, Maintenance & Upgrade
Power Requirements	DC12V
Power Consumption	<4W
Operating Temperature	-10°C – 60°C
Operating Humidity	90% RH Max
Ingress Protection	4000V Thunder, Surge & Wave Protection
Dimensions	64.43mm x 145.02mm
Weight	0.9 lbs approx.
Shipping Weight	1.05 lbs approx.

Product Specifications

IPOF-EL1MPIR30-W



1.3 MP



WiFi[®]

Day
Night

Smart Phone

2-Way
Audio