

Product Specifications

NVR-ELC-16

Features:

- 16 IP camera inputs
- 1/1ch Mic in/out
- Compatible with 5MP, 3MP, 1080P, 720P, D1 and etc.
- HDMI, VGA output up to 1080P, 1 TV
- 16ch alarm in & 6ch relay out, RS485, RS232
- 4 SATA, 3 USB, 1 RJ45 (1000Mbps)



| | |
|-------------------------|---|
| Main Processor | Dual-core embedded processor |
| Operating System | Embedded LINUX |
| IP Camera Input | 16 channel |
| Two-way Talk | 1 channel Input, 1 channel Output, BNC |
| Interface | 1 HDMI, 1 VGA, 1TV |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 |
| Display Split | 1/4/8/9/16 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection |
| Compression | H.264 / MJPEG |
| Resolution | 5MP(2560 x 1920) 3MP(2048×1536) 1080P(1920×1080) 720P(1280×720) D1(704×576/704×480) |
| Record Rate | Max 128Mbps |
| Bit Rate | 48~ 8192kbps |
| Record Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, |
| Trigger Events | Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera |
| Alarm Input | 16 channel |
| Relay Output | 6 channel |
| Sync Playback | 1/4/9/16 |

